



ABC Adventure Buggy Company Reclining Toddler Seat for Twin Pram Instructions for Correct Use

Read these instructions carefully before use and keep for future reference.

Your child's safety may be affected if you do not follow these instructions.





CORRECT INSTALLATION FOR THE ABC RECLINING/NEWBORN TODDLER SEAT ONTO THE ABC TWIN ADVENTURE BUGGY

**CAUTION: MAXIMUM WEIGHT CAPACITY;
RECLINING TODDLER SEAT 25kg**



CAUTION: The Reclining Newborn/Toddler Seat (R-T/S) adaptor bar is required to rest against the top of the buggy frame for correct balance and stability. The R-T/S must be positioned directly over the buggies rear wheels.

CAUTION: The ABC 4 Wheel Stability Kit must be used on the Single ABC Buggy when adding the attachment of the ABC Toddler Seats.

REMOVE THE HANDLE BAR FROM THE BUGGY

- 1) Unclip the top press-studs on the canopy and top of buggy sling / seat.
- 2) First apply the brake. Then loosen the tri-knobs at the base of the handle bar, pull the handle out to the end and two springs will spring into position. Depress the spring buttons on the side of the frame one at a time and also pulling the handle each side as you go.
- 3) Remove the handle bar from the buggy frame.

INSTALLING THE ADAPTOR BAR ONTO THE EXTENDIBLE HANDLE

- 1) With the Adaptor bar prongs for toddler seat facing you, enter the extendible handle bar into the tube brackets of the Adaptor Bar.
- 2) Slide the handle through the Adaptor bar tube openings (note: you will have to depress the safety buttons on the handle to complete the process).

RETURN THE HANDLE/ADAPTOR BAR ONTO THE BUGGY

- 1) Ensure your sun canopy is out stretched into the sun protection position.
- 2) Slide the Adaptor bar half way up the handle.
- 3) With the Adaptor Bar now installed on to the extendible handle, return the handle/Adaptor Bar combination to the buggy.
- 4) Ensure the safety buttons have clicked into the safety holes of the buggy frame (which is the fully extended position of the handle).
- 5) Attach the R-T/S to the Adaptor Bar, depressing the spring lock buttons on the Adaptor Bar to allow the R-T/S to sit at the base of the adaptor bar prongs.
- 6) **IMPORTANT:** Slide the Adaptor Bar down the handle so that the Adaptor bars tube brackets are flush with the TOP of the buggy frame.

NOTE: The Adaptor Bar is required to rest against the top of the buggy frame for correct balance and stability. The R-T/S must be positioned directly over the buggies rear wheels.

- 7) Tighten the tri-knob screws under the handle bar to secure the handle into place.

Please click on this link to view [Demonstration Videos](#)



**To remove the seat - simply reverse the above instructions for installing.
PLACING YOUR CHILD INTO THE RECLINING NEWBORN/TODDLER
SEAT**

- 1) Apply the brake of the buggy.
- 2) Un-dome the front crotch “tongue” and raise the safety bar slightly to permit your infants legs to pass under.
- 3) Place your child fully in the seat.
- 4) Ensure the crotch “tongue” is re-domed over the safety bar.
- 5) Apply and adjust the 5-point safety harness, ensuring your toddler is adequately and safely restrained.



NEVER, UNDER ANY CIRCUMSTANCES LEAVE YOUR CHILDREN UNATTENDED IN THE BUGGY.

“TO CARE, YOU HAVE TO BE THERE!!!”

IF YOU MUST LEAVE THE BUGGY UNATTENDED – FIRST REMOVE YOUR CHILD FROM THE R-T/S.

KERB CAUTION: Extreme care is necessary when moving from the pavement, down a kerb and onto the road.

CAUTION: THE TODDLER SEAT IS NOT TO BE USED FOR JOGGING IN ANY CIRCUMSTANCES - WALKING PACE ONLY

EXTREME CAUTION IS ADVISED AT ALL TIMES WHEN USING THIS PRODUCT



Australian Distributor

Brand Style
PO Box 194
St Kilda
Victoria 3182

Ph: 1300 992 354
Email: info@brandstyle.com.au
Web: www.banstyle.com.au

Manufacturer

68A Cambridge St South
Levin
New Zealand

Email: abcbuggy@xtra.co.nz
Web: www.adventurebuggycompany.com